RZR Pro XP Sport White Lightning





Key Specifications

 181
 64"
 14.5"*

 HP
 WIDTH
 GROUND CLEARANCE

Engine & Drivetrain

Cooling	Liquid
Cylinders Displacement	925cc
Drive System Type	Isolated Xtreme Performance True On-Demand AWD/2WD
Engine Braking System (EBS)	Not Equipped
Engine Type	4-Stroke DOHC Twin Cylinder Turbocharged
Fuel System/Battery	Electronic Fuel Injection
Horsepower	181 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H

Dimensions

Bed Box Dimensions (L x W x H)	26 x 17.7 x 11.5 in (66 x 45 x 29.2 cm)
Box Capacity	300 lb (136.1 kg)
Estimated Dry Weight	1,760 lbs (796Kg)
Fuel Capacity	12 gal (45.4 L)
Ground Clearance	14.5 in (36.8 cm)
Overall Vehicle Size (L x W x H)	126 x 64 x 71.7 in (320 x 162.6 x 182.1 cm)
Payload Capacity	740 lb (336 kg)
Wheelbase	96 in (244 cm)

Brakes

Front/Rear Brakes	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers
Parking Brake	Park In-Transmission

Additional Specifications

Cargo System	Lock & Ride
Doors	Vented Full Doors
Electronic Power Steering	High Assist Electronic Power Steering with Quick Turn Rack; Race Inspired Steering Wheel
Hitch Towing Rating	N/A
Hitch Type	Not Equipped
Instrumentation	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet
Lighting	White LED Low/High & Red LED Tail / Brake Lights
Other Standard Features	High Output 900w charging system with sealed electrical, Polaris Pulse system, In-Dash Charge Port, Polaris P.A.S.S.
Seat Type	Bolstered Bucket Seats with 4-way adjustability and Height Adjustable Seat Belts

Tires / Wheels

Front Tires	30 x 10-14 MAXXIS Carnivore; Wheel Size 14x6
Rear Tires	30 x 10-14 MAXXIS Carnivore; Wheel Size 14x7
Wheels	Cast Aluminum

Suspension

Electronic Suspension Control System	N/A
Front Shocks	2 in Walker Evans Needle Shocks with 16-Position Adjustable Clickers
Front Suspension	High-Clearance Dual A-Arm with Stabilizer Bar and 20 in (50.8 cm) Usable Travel*, 17 in (43.2 cm) Wheel Travel
Rear Shocks	2.5 in Walker Evans Needle Shocks with 16-Position Adjustable Clickers
Rear Suspension	Trailing Arm & Standard-Clearance Radius Rods with Stabilizer Bar and 22 in (55.9 cm) Usable Travel*,