## **RZR Pro XP Ultimate Super Graphite**





#### **Key Specifications**

181 64" 14.5"\*

HP WIDTH GROUND CLEARANCE

## **Engine & Drivetrain**

| Cooling                     | Liquid   |  |
|-----------------------------|--|--|
| Cylinders Displacement      | 925cc  |  |
| Drive System Type           | Isolated Xtreme Performance True On-Demand AWD/2WD |  |
| Engine Braking System (EBS) | Not Equipped                                       |  |
| Engine Type                 | 4-Stroke DOHC Twin Cylinder Turbocharged           |  |
| Fuel System/Battery         | Electronic Fuel Injection                          |  |
| Horsepower                  | 181 HP   |  |
| Transmission/Final Drive    | Automatic PVT P/R/N/L/H                            |  |

#### **Dimensions**

| Bed Box Dimensions (L x W x H)   | 26 x 17.7 x 11.5 in (66 x 45 x 29.2 cm)     |
|----------------------------------|---|
| Box Capacity                     | 300 lb (136.1 kg)                           |
| Estimated Dry Weight             | 1,795 lb (814 kg)                           |
| Fuel Capacity                    | 12 gal (45.4 L)                             |
| Ground Clearance                 | 14.5 in (36.8 cm)                           |
| Overall Vehicle Size (L x W x H) | 126 x 64 x 71.7 in (320 x 162.6 x 182.1 cm) |
| Payload Capacity                 | 740 lb (336 kg)                             |
| Wheelbase                        | 96 in ( 244 cm)                             |
|                                  |   |

#### **Brakes**

| Front/Rear Brakes | 4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers |
|-------------------|---|
| Parking Brake     | Park In-Transmission  |

# **Additional Specifications**

| Cargo System              | Lock & Ride Full Door   |  |  |
|---------------------------|---|--|--|
| Doors                     |   |  |  |
| Electronic Power Steering | High Assist Electronic Power Steering with Quick Turn Rack; Race inspired Steering Wheel with Tilt and Telescoping adjustment; Dynamix and Ride Command Push Button Controls  |  |  |
| Hitch Towing Rating       | N/A   |  |  |
| Hitch Type                | Not Equipped  |  |  |
| Instrumentation           | RIDE COMMAND® 7" Glove-Touch Display: DYNAMIX 2.0 Visualizer, Digital Instrumentation, Built-In GPS, Group ride (cell-based or GPS based), Topographic Mapping, Bluetooth & USB Smartphone Connectivity, AM/FM & Weather Radio, In-Vehicle Communications Capable With Optional Sena Headsets, Rockford   |  |  |
|                           | Fosgate Premium Audio (Including 2 Tweeters, 2 Front Speakers, and External 400W Amp) Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet |  |  |
| Lighting                  | Signature White LED, Low/High & Red LED Tail / Brake Lights;<br>Front, Rear, and Interior Accent Lighting   |  |  |
| Other Standard Features   | High Output 900w charging system with sealed electrical, Polaris Pulse system, In-Dash Charge Port, USB Charging, Polaris P.A.S.S.  |  |  |
| Seat Type                 | Bolstered Bucket Seats with 4-way adjustability (including 6" front to back toolless seat slider with tilt adjustability) and Retractable Click 6 Harnesses   |  |  |

### Tires / Wheels

| Front Tires | 30 x 10-14 MAXXIS Carnivore (8-Ply); Wheel Size 14x6 |  |
|-------------|--|--|
| Rear Tires  | 30 x 10-14 MAXXIS Carnivore (8-Ply); Wheel Size 14x7 |  |
| Wheels      | Cast Aluminum  |  |

## Suspension

| Electronic Suspension Control System | DYNAMIX 2.0 Active Suspension System   |
|--------------------------------------|--|
| Front Shocks                         | FOX 2.5 Podium Live Valve with Bottom-Out Control (Electronically Controlled Damping)  |
| Front Suspension                     | High-Clearance Dual A-Arm with Stabilizer Bar and 20 in (50.8 cm) Usable Travel*, 17 in (43.2 cm) Wheel Travel                 |
| Rear Shocks                          | FOX 2.5 Podium Live Valve with Bottom-Out Control (Electronically Controlled Damping)  |
| Rear Suspension                      | Trailing Arm & High-Clearance Radius Rods with Stabilizer Bar and 22 in (55.9 cm) Usable Travel*, 20 in (50.8 cm) Wheel Travel |