

RZR XP 1000 Premium Black Pearl



Key Specifications

110

HP

64"

WIDTH

14"

GROUND CLEARANCE

Engine & Drivetrain

Cooling	Liquid
Cylinders Displacement	999cc
Drive System Type	High Performance True On-Demand AWD/2WD
Engine Braking System (EBS)	Not Equipped
Engine Type	4-Stroke DOHC Twin Cylinder
Fuel System/Battery	Electronic Fuel Injection
Horsepower	110 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H

Dimensions

Bed Box Dimensions (L x W x H)	28 x 22 x 7 in (72.0 x 57.0 x 17.8 cm)
Box Capacity	300 lb (136.1 kg)
Estimated Dry Weight	1,460 lbs (667 kg)
Fuel Capacity	9.5 gal (35.9 L)
Ground Clearance	14 in (35.6 cm)
Overall Vehicle Size (L x W x H)	119 x 64 x 73.75 in (302.2 x 162.6 x 187.3 cm)
Payload Capacity	740 lb (336 kg)
Wheelbase	90 in (228.6 cm)

Brakes

Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers
Parking Brake	Park In-Transmission

Additional Specifications

Cargo System	Lock & Ride
Doors	Bowed 1/4 Doors
Electronic Power Steering	Standard with Quick Turn Rack
Hitch Towing Rating	N/A
Hitch Type	Not Equipped
Instrumentation	RIDE COMMAND® 7" Glove-Touch Display: Digital Instrumentation, Built-In GPS, Group ride (cell-based or GPS based), Topographic Mapping, Bluetooth & USB Smartphone Connectivity, AM/FM & Weather Radio, In-Vehicle Communications Capable With Optional Sena Headsets Speedometer, Odometer, Tripmeter, Tachometer, Coolant Temperature, Volt Meter, Hour Meter, Service Indicator, Clock, Gear Indicator, Fuel Gauge, Hi-Temp Light, Seatbelt Reminder Light, Fault Code Display, DC Outlet, Ambient Temp
Lighting	Front Blacked Out Signature White LED Low/High with Accent Lights & Red LED Tail / Brake Lights
Other Standard Features	MB Quart Door Speakers & Rear Wired Camera
Seat Type	Bolstered Bucket Seats with Driver Seat Slider and Height Adjustable Seat Belts

Tires / Wheels

Front Tires	29 x 9-14; Radial Tire
Rear Tires	29 x 11-14; Radial Tire
Wheels	Cast Aluminum

Suspension

Electronic Suspension Control System	Not Equipped
Front Shocks	2 in Walker Evans Needle Shocks with 16-Position Adjustable Clickers
Front Suspension	Dual A-Arm with Stabilizer Bar and 20 in (50.8 cm) Usable Travel*, 16 in (40.6 cm) of Wheel Travel
Rear Shocks	2.5 in Walker Evans Needle Shocks with 16-Position Adjustable Clickers
Rear Suspension	Trailing Arm with Stabilizer Bar and 20 in (50.8 cm) Usable Travel*, 18 in (45.7 cm) of Wheel Travel