

RZR XP 1000 Sport Cruiser Black



Key Specifications

110
HP

64"
WIDTH

14"
GROUND CLEARANCE

Engine & Drivetrain

Cooling	Liquid
Cylinders Displacement	999cc
Drive System Type	High Performance True On-Demand AWD/2WD
Engine Braking System (EBS)	Not Equipped
Engine Type	4-Stroke DOHC Twin Cylinder
Fuel System/Battery	Electronic Fuel Injection
Horsepower	110 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H

Dimensions

Bed Box Dimensions (L x W x H)	28 x 22 x 7 in (72.0 x 57.0 x 17.8 cm)
Box Capacity	300 lb (136.1 kg)
Estimated Dry Weight	1,460 lbs (662 kg)
Fuel Capacity	9.5 gal (35.9 L)
Ground Clearance	14 in (35.6 cm)
Overall Vehicle Size (L x W x H)	119 x 64 x 73.75 in (302.2 x 162.6 x 187.3 cm)
Payload Capacity	740 lb (336 kg)
Wheelbase	90 in (228.6 cm)

Brakes

Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers
Parking Brake	Park In-Transmission

Additional Specifications

Cargo System	Lock & Ride
Doors	Bowed 1/4 Doors
Electronic Power Steering	Standard with Quick Turn Rack
Hitch Towing Rating	N/A
Hitch Type	Not Equipped
Instrumentation	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet
Lighting	Signature White LED, Low/High & Red LED Tail / Brake Lights
Other Standard Features	N/A
Seat Type	Bolstered Bucket Seats with Driver Seat Slider and Height Adjustable Seat Belts

Tires / Wheels

Front Tires	29 x 9-14; Radial Tire
Rear Tires	29 x 11-14; Radial Tire
Wheels	Cast Aluminum

Suspension

Electronic Suspension Control System	Not Equipped
Front Shocks	2 in Walker Evans Needle Shocks with 16-Position Adjustable Clickers
Front Suspension	Dual A-Arm with Stabilizer Bar and 20 in (50.8 cm) Usable Travel*, 16 in (40.6 cm) of Wheel Travel
Rear Shocks	2.5 in Walker Evans Needle Shocks with 16-Position Adjustable Clickers
Rear Suspension	Trailing Arm with Stabilizer Bar and 20 in (50.8 cm) Usable Travel*, 18 in (45.7 cm) of Wheel Travel