

# RZR XP 1000 Sport Polaris Blue



## Key Specifications

**110**  
HP

**64"**  
WIDTH

**14"**  
GROUND CLEARANCE

## Engine & Drivetrain

Cooling	Liquid
Cylinders Displacement	999cc
Drive System Type	High Performance True On-Demand AWD/2WD
Engine Braking System (EBS)	Not Equipped
Engine Type	4-Stroke DOHC Twin Cylinder
Fuel System/Battery	Electronic Fuel Injection
Horsepower	110 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H

## Dimensions

Bed Box Dimensions (L x W x H)	28 x 22 x 7 in (72.0 x 57.0 x 17.8 cm)
Box Capacity	300 lb (136.1 kg)
Estimated Dry Weight	1,460 lbs (662 kg)
Fuel Capacity	9.5 gal (35.9 L)
Ground Clearance	14 in (35.6 cm)
Overall Vehicle Size (L x W x H)	119 x 64 x 73.75 in (302.2 x 162.6 x 187.3 cm)
Payload Capacity	740 lb (336 kg)
Wheelbase	90 in ( 228.6 cm)

## Brakes

Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers
Parking Brake	Park In-Transmission

## Additional Specifications

<b>Cargo System</b>	Lock & Ride
<b>Doors</b>	Bowed 1/4 Doors
<b>Electronic Power Steering</b>	Standard with Quick Turn Rack
<b>Hitch Towing Rating</b>	N/A
<b>Hitch Type</b>	Not Equipped
<b>Instrumentation</b>	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet
<b>Lighting</b>	Signature White LED, Low/High & Red LED Tail / Brake Lights
<b>Other Standard Features</b>	N/A
<b>Seat Type</b>	Bolstered Bucket Seats with Driver Seat Slider and Height Adjustable Seat Belts

## Tires / Wheels

<b>Front Tires</b>	29 x 9-14; Radial Tire
<b>Rear Tires</b>	29 x 11-14; Radial Tire
<b>Wheels</b>	Cast Aluminum

## Suspension

<b>Electronic Suspension Control System</b>	Not Equipped
<b>Front Shocks</b>	2 in Walker Evans Needle Shocks with 16-Position Adjustable Clickers
<b>Front Suspension</b>	Dual A-Arm with Stabilizer Bar and 20 in (50.8 cm) Usable Travel*, 16 in (40.6 cm) of Wheel Travel
<b>Rear Shocks</b>	2.5 in Walker Evans Needle Shocks with 16-Position Adjustable Clickers
<b>Rear Suspension</b>	Trailing Arm with Stabilizer Bar and 20 in (50.8 cm) Usable Travel*, 18 in (45.7 cm) of Wheel Travel