

# RZR XP 4 1000 Premium Indy Red



## Key Specifications

**110**  
HP

**64"**  
WIDTH

**14"**  
GROUND CLEARANCE

## Engine & Drivetrain

Cooling	Liquid
Cylinders Displacement	999cc
Drive System Type	High Performance True On-Demand AWD/2WD
Engine Braking System (EBS)	Not Equipped
Engine Type	4-Stroke DOHC Twin Cylinder
Fuel System/Battery	Electronic Fuel Injection
Horsepower	110 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H

## Dimensions

Bed Box Dimensions (L x W x H)	28 x 22 x 7 in (72.0 x 57.0 x 17.8 cm)
Box Capacity	300 lb (136.1 kg)
Estimated Dry Weight	1,681 lbs (762 kg)
Fuel Capacity	9.5 gal (35.9 L)
Ground Clearance	14 in (35.6 cm)
Overall Vehicle Size (L x W x H)	146 x 64 x 73.75 in (370.8 x 162.6 x 187.3 cm)
Payload Capacity	900 lb (408 kg)
Wheelbase	117 in (297.2 cm)

## Brakes

Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers
Parking Brake	Park In-Transmission

## Additional Specifications

<b>Cargo System</b>	Lock & Ride
<b>Doors</b>	Bowed 1/4 Doors
<b>Electronic Power Steering</b>	Standard with Quick Turn Rack
<b>Hitch Towing Rating</b>	N/A
<b>Hitch Type</b>	Not Equipped
<b>Instrumentation</b>	RIDE COMMAND® 7" Glove-Touch Display: Digital Instrumentation, Built-In GPS, Group ride (cell-based or GPS based), Topographic Mapping, Bluetooth & USB Smartphone Connectivity, AM/FM & Weather Radio, In-Vehicle Communications Capable With Optional Sena Headsets Speedometer, Odometer, Tripmeter, Tachometer, Coolant Temperature, Volt Meter, Hour Meter, Service Indicator, Clock, Gear Indicator, Fuel Gauge, Hi-Temp Light, Seatbelt Reminder Light, Fault Code Display, DC Outlet, Ambient Temp
<b>Other Standard Features</b>	MB Quart Door Speakers & Rear Wired Camera
<b>Seat Type</b>	Bolstered Bucket Seats with Driver Seat Slider and Height Adjustable Seat Belts

## Tires / Wheels

<b>Front Tires</b>	29 x 9-14; Radial Tire
<b>Rear Tires</b>	29 x 11-14; Radial Tire
<b>Wheels</b>	Cast Aluminum

## Suspension

<b>Electronic Suspension Control System</b>	Not Equipped
<b>Front Shocks</b>	2 in Walker Evans Needle Shocks with 16-Position Adjustable Clickers
<b>Front Suspension</b>	Dual A-Arm with Stabilizer Bar and 20 in (50.8 cm) Usable Travel*, 16 in (40.6 cm) of Wheel Travel
<b>Rear Shocks</b>	2.5 in Walker Evans Needle Shocks with 16-Position Adjustable Clickers
<b>Rear Suspension</b>	Trailing Arm with Stabilizer Bar and 20 in (50.8 cm) Usable Travel*, 18 in (45.7 cm) of Wheel Travel