Sportsman 570 Desert Sand





Key Specifications

 48"
 44
 11.5"

 WIDTH
 HP
 GROUND CLEARANCE

Engine & Drivetrain

Active Descent Control	Not Equipped
Cooling	Liquid
Cylinders Displacement	567cc
Drive System Type	One Touch On-Demand AWD/2WD
Engine Braking System (EBS)	Not Equipped
Engine Type	ProStar 4-Stroke DOHC Single Cylinder
Fuel System/Battery	Electronic Fuel Injection / 340 CCA
Horsepower	44 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H In-line Shifting

Dimensions

N/A
705 lb (319.8 kg)
90 lb /180 lb (40.8 kg /81.6 kg)
4.5 gal (17.0 L)
11.5 in (29 cm)
83 x 48 x 47 in (210.8 x 121.9 x 119.4 cm)
485 lb (220 kg)
1
33.75 in (85.7 cm)
50.5 in (128.3 cm)

Brakes

FIUIIVITEAL DIANES	Siligle Level 3-vvileel Hyulaulic Disc Willi Hyulaulic Real Foot blake
Parking Brake	Park In-Transmission / Lockable Hand Lever

Specifications

Cargo System	Lock & Ride Compatible 5 Gal (18.9L) Front Dry Storage
Front Suspension	Sealed MacPherson Strut With 8.2 in (20.8 cm) Travel
Hitch Towing Rating	1,350 lb (612 kg)
Hitch Type	Standard 1.25 in (3.2 cm) Receiver
Instrumentation	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light
Lighting	
	Halogen Pod & Bumper Lights, Triple 50w High Beams, Dual 50w Low Beams, Single LED Brake Light/Taillight
Other Standard Features	Front Rack Extender, 12 Volt Power Plug, Pre-Wired for Hand & Thumb Warmers, In Pod Battery Charger, Winch Mount Included
Rear Suspension	Sealed Dual A-Arm, IRS 9.5 in (24.1 cm) Travel

Tires / Wheels

Electronic Power Steering	Not Equipped
Front Tires	25x8-12 P373; 6 PLY
Rear Tires	25x10-12 P373; 6 PLY
Wheels	Steel