

Sportsman 570 EPS Zenith Blue

SPORTSMAN



Key Specifications

48"
WIDTH

44
HP

11.5"
GROUND CLEARANCE

Engine & Drivetrain

Active Descent Control	Not Equipped
Cooling	Liquid
Cylinders Displacement	567cc
Drive System Type	One Touch On-Demand AWD/2WD
Engine Braking System (EBS)	Equipped
Engine Type	ProStar 4-Stroke DOHC Single Cylinder
Fuel System/Battery	Electronic Fuel Injection / 340 CCA
Horsepower	44 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H In-line Shifting

Dimensions

Bed Box Dimensions (L x W x H)	N/A
Estimated Dry Weight	753 lb (342 kg)
Front/Rear Rack	90 lb /180 lb (40.8 kg /81.6 kg)
Fuel Capacity	4.5 gal (17.0 L)
Ground Clearance	11.5 in (29 cm)
Overall Vehicle Size (L x W x H)	83 x 48 x 47 in (210.8 x 121.9 x 119.4 cm)
Payload Capacity	485 lb (220 kg)
Person Capacity	1
Seat Height	33.25 in (84.5 cm)
Wheelbase	50.5 in (128.3 cm)

Brakes

Front/Rear Brakes	Single Lever 3 Wheel Hydraulic Disc with Hydraulic Rear Foot Brake
-------------------	--

Front/Rear Brakes	Single Lever 3-wheel Hydraulic Disc with Hydraulic Rear Foot Brake
Parking Brake	Park In-Transmission / Lockable Hand Lever

Specifications

Cargo System	Lock & Ride Compatible 5 Gal (18.9L) Front Dry Storage
Front Suspension	Sealed MacPherson Strut With 8.2 in (20.8 cm) Travel
Hitch Towing Rating	1,350 lb (612 kg)
Hitch Type	Standard 1.25 in (3.2 cm) Receiver
Instrumentation	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Clock
Lighting	Halogen Pod & Bumper Lights, Triple 50w High Beams, Dual 50w Low Beams, Twin LED Brake Lights/Taillights
Other Standard Features	Front Trail Bumper, Front and Rear Rack Extenders, 12 Volt Power Plug, Pre-Wired for Hand & Thumb Warmers, In Pod Battery Charger, Winch Mount Included
Rear Suspension	Sealed Dual A-Arm, IRS 9.5 in (24.1 cm) Travel

Tires / Wheels

Electronic Power Steering	Multi Select EPS
Front Tires	25x8-12 P373; 6 PLY
Rear Tires	25x10-12 P373; 6 PLY
Wheels	Steel